

Quick Check® 200 Series

Bar Code Verifier by 



Features

- Program 'Test Bar Code Specifications' by simply scanning a command code
- Traceable to NIST (National Institute of Standards and Technology)
- Follows the ISO15416 and ANSI X3.182 Bar Code Inspection Method (optional mouse or pen wand only)
- Conforms to ISO15426-1 Bar Code Verifier Specification (optional mouse or pen wand only)
- Auto-discriminates between all popular symbologies
- Bidirectional scanning
- Multiple scan averaging
- Traditional analysis also provided

The Quick Check® 200 Series is the lowest price ISO/ANSI method verifier from HHP. It provides full traditional and ISO/ANSI analysis, reflectance, and format tests. These models perform quick pass/fail tests or use more powerful measuring tools for highly detailed analysis. The unit is also RS-232 compatible and works with a Windows®-based verification software package. Repeatability between units is outstanding, making the Quick Check® 200 series a good entry level ISO/ANSI method verifier.

The Quick Check® 200 series is the lowest price verifier from HHP

The Quick Check® 200 series meets the International Organization for Standardization's "Bar Code Print Quality Test Specification (ISO 15416), the American National Standard Institute's "Guideline for Bar Code Quality" (ANSI X3.182-1990), the Uniform Code Council (UCC), and the CEN specifications regarding verification methods and methodology. It also meets International Organization for Standardization's "Bar Code Verifier Conformance Specification" (ISO 15426-1).

Quick Check® verifiers are easy to use, yet packed with high performance features that utilize the most sophisticated test methods. All the popular linear symbologies are supported. AutoPrint/Store capability, multiple scan averaging and sub-symbology choices are easily accessed through a three-button user interface. Analysis information appears immediately on a 1 line by 12-character alphanumeric liquid crystal display (LCD). A distinct audible tone and a series of five colored LED's indicate whether a bar code is in or out of specification.

To accommodate varying label densities, choose from 5, 6, and 10 mil sizes,

If needed, a detailed hard copy printout can be produced from the Quick Check® 200 using an optional direct thermal printer or inspection data can also be sent to computer using an optional VCI option. This allows verification results to be printed, saved, or transferred to other applications.

This equipment and its documentation were developed to fit into your company's existing ISO 9000/9001/9002 policies and procedures.



www.autoidsolutions.net

Sales, Support, and Calibration +1.866.828.8643
701 Decatur Ave N 106, Minneapolis, MN 55427

Quick Check® 200 Series

Features

ISO/ANSI scan profile test method	Y
Instant "On-Screen" ISO/ANSI grade	Y
ISO/ANSI 10-scan grade averaging	Y
Traditional test method	Y
Special reflectometer mode	Y
Auto-switch Symbologies	Y
Change aperture/wavelength from menu	N
Automatic power off	Y
Data buffer	Y
Command code programming	Y
Detail hardcopy printout (optional)	Y

Verification Methods

Parameters determined by ISO/ANSI bar code print quality guidelines and traditional pass/fail criteria. Refer to model matrix below for configurations.

	QC 200	QC 210	QC 220	QC 230	QC 250
ISO	Y	Y	Y	Y	Y
ANSI	Y	Y	Y	Y	Y
Traditional	Y	Y	Y	Y	Y
Industry Applications:					
SCC Retail	N	Y	Y	Y	Y
U.P.C Coupon Code	N	Y	N	N	Y
AIAG (Automotive)	N	N	N	Y	Y
LOGMARS (Government)	N	N	N	Y	Y
HIBCC (Health)	N	N	Y	N	Y
SISAC (Serials Coding)	N	Y	N	N	Y
CTIA/ABCD (Computer)	N	N	N	Y	Y
Bookland (Books)	N	Y	N	N	Y
CCBBA (Blood Bank)	N	N	Y	N	Y

Dimensions

Height:	1.6 in. (4.2 cm)
Width:	1.8 in. (4.6 cm)
Length:	7.1 in. (18.3 cm)

Mechanical

Weight:	5.5 ounces (156 g)
Power:	AC Charger
Case:	Lexan polycarbonate 141
Beeper:	A single beeper provides an audible valid/invalid signal and a triple beep on known out of spec codes
Display:	1 line X 12 character LCD
Keypad:	3-button, power, scroll, select
LEDs:	2 LEDs (one red and one green)

Environmental

Operating Temperature:	32 to 122° F (0 to 50° C)
Storage Temperature:	14 to 158° F (-20 to 70°C)
Relative Humidity:	5% to 95% Non-condensing

Optical

When ordering Quick Check 200 Series verifiers, choose the applicable aperture size and wavelength

Test Aperture:	5, 6, or 10 mil
Wavelength:	Visible: 660nm Infrared: 940nm

Symbologies

EAN/UPC with addenda, Code 39, Interleaved 2 of 5, Codabar, Code 128, MSI, Code 16K, Regular 2 of 5 (Discrete/Industrial 2 of 5), IATA 2 of 5 (Straight 2 of 5)

Safety/Regulatory

FCC Class A, CE Certified



Quick Check is a registered trademark of Hand Held Products Corporation in the United States and/or other countries.



www.autoidsolutions.net
Sales, Support, and Calibration +1.866.828.8643
701 Decatur Ave N 106, Minneapolis, MN 55427