

Inspector® 4000 Series

Bar Code Verifier by 



Features

- Multiple apertures and light wavelengths (set via menu selections)
- Traceable to NIST (National Institute of Standards and Technology)
- Follows the ISO15416 and ANSI X3.182 Bar Code Inspection Method
- Conforms to ISO15426-1 Bar Code Verifier Specification
- Auto-discriminates between all popular symbologies
- Bidirectional scanning
- Multiple scan averaging
- Traditional analysis also provided

An I-4000 patented Auto-Optic scanner is the best value ISO/ANSI method verifier from RJS. Key features include a patented Auto-Optic scan head that allows for eight optical arrangements settable via menu selections for four aperture sizes and two wavelengths of light. The patented Auto-Optic scanner is designed and manufactured by RJS for the sole purpose of performing ISO/ANSI method bar code quality analysis. Repeatability between units is outstanding, making the I-4000 an ideal choice for a standardized company-wide ISO/ANSI method verifier.

NOTE: This model is only recommended for existing I-4000 applications or new applications involving Code 93 symbols. For all other new applications the Inspector D4000 with an Auto-Optic option is recommended.

The Inspector® 4000 is the best value ISO/ANSI verifier from RJS

The Inspector® I-4000 meets the International Organization for Standardization's "Bar Code Print Quality Test Specification (ISO 15416), the American National Standard Institute's "Guideline for Bar Code Quality" (ANSI X3.182-1990), the Uniform Code Council (UCC), and the CEN specifications regarding verification methods and methodology. It also meets International Organization for Standardization's "Bar Code Verifier Conformance Specification" (ISO 15426-1).

This truly unique and powerful instrument is also easy to use. All the popular linear symbologies are supported. Store and print capability, multiple scan averaging and sub-symbology choices are easily accessed through a simple four-button user interface. Analysis information appears immediately on a 32-character alphanumeric liquid crystal display (LCD). A distinct audible tone and a series of five colored LED's indicate whether a bar code is in or out of specification. In addition to the ISO/ANSI method parameters, traditional analysis parameters are provided on the LCD without a special mode setting.

Two patented Auto-Optic scan head versions are available; 3, 6, 10, 20 mil or 3, 5, 10, 20 mil aperture choices. Both versions provide red (660 nm) and infrared (925nm) light wavelength selections.

If needed, a detailed hard copy printout can be produced from the Inspector® I-4000 using an optional direct thermal printer or inspection data can also be sent to computer using an optional VCI option. This allows verification results to be printed, saved, or transferred to other applications.

This equipment and its documentation were developed to fit into your company's existing ISO 9000/9001/9002 policies and procedures.



www.autoidsolutionsinc.com

Sales, Support, and Calibration +1.866.828.8643
16425 39th Place North, Minneapolis, MN 55446

Inspector® 4000 Series

Features

ISO/ANSI scan profile test method	Y
Instant "On-Screen" ISO/ANSI grade	Y
ISO/ANSI 10-scan grade averaging	Y
Traditional test method	Y
Special reflectometer mode	Y
Auto-switch Symbologies	Y
Change aperture/wavelength from menu	Y
Automatic power off	Y
Data buffer	Y
Command code programming	N
Detail hardcopy printout (optional)	Y

Verification Methods

Parameters determined by ISO/ANSI bar code print quality guidelines and traditional pass/fail criteria. Refer to model matrix below for configurations.

	<u>Auto-Optic</u>
ISO	Y
ANSI	Y
Traditional	Y
Industry Applications:	
SCC Retail	Y
U.P.C Coupon Code	Y
AIAG (Automotive)	Y
LOGMARS (Government)	Y
HIBCC (Health)	Y
SISAC (Serials Coding)	N
CTIA/ABCD (Computer)	N
Bookland (Books)	Y
CCBBA (Blood Bank)	N

Dimensions

Height:	1.9 in. (4.8 cm)
Width:	4.6 in. (11.7 cm)
Length:	7.8 in. (19.8 cm)

Mechanical

Weight:	16 ounces (454 g)
Power:	4 AA NiCad batteries and AC Charger
Case:	Acrylonitrile Butadiene Styrene (ABS)
Beeper:	Audible tones indicate an audible pass/fail and low battery
Display:	4 line X 8 character LCD
Keypad:	4-button, on, select, enter, print
LEDs:	5 LEDs (two red, one yellow, and two green)

Environmental

Operating Temperature:	32 to 122° F (0 to 50° C)
Storage Temperature:	14 to 158° F (-20 to 70° C)
Relative Humidity:	5% to 95% Non-condensing

Optical

Test Aperture:	Auto-Optic option A: 3, 5, 10, or 20 mil Auto-Optic option B: 3, 6, 10, or 20 mil
Wavelength:	Visible: 660nm Infrared: 925nm

Symbologies

EAN/UPC with addenda, Code 39, Interleaved 2 of 5, Codabar, Code 128, Regular 2 of 5 (Discrete/Industrial 2 of 5), Code 93

Safety/Regulatory

FCC Class A, CE Certified



Inspector is a registered trademark of Printronix Corporation in the United States and/or other countries.



www.autoidsolutionsinc.com
Sales, Support, and Calibration +1.866.828.8643
16425 39th Place North, Minneapolis, MN 55446