

Inspector® and Quick Check Series Printer

Bar Code Printer for  and 



Features

- Direct thermal printer
- 203 DPI/8 dots per mm resolution
- 4 inch print width
- Compatible verifiers:
 - ✓ RJS Laser Inspector 1000
 - ✓ RJS Inspector 2000
 - ✓ RJS Inspector 3000
 - ✓ RJS Inspector 4000
 - ✓ RJS Inspector D4000
 - ✓ HHP Quick Check 600
 - ✓ HHP Quick Check 800

```
INSPECTOR 3000
Revision B.01
10-Scan Average Analysis
Intervald 2of5
010101


Scan Profile Analysis
Reference Decod...A
Decodability...82%...A
Symbol Contrast...71%...A
Refl(MIN)/Refl(MAX)...0%...A
Edge Contrast(MIN)...35%...A
Modulation...49%...D
Defects...07%...A
Application Compliance...A

OVERALL SYMBOL GRADE
C/10/600 1.6/10/600

Traditional Analysis
Acceptable
-100% Tol. +100%
-----+R+++++

Wide/Narrow Ratio...2.7 PASS
Print Contrast Signal...91% PASS
Required POS...75%
Element Refl.(MAX)...69% PASS
Reflectance(MIN)...00% PASS

Pass/Fail Analysis
Passing Grade Selected...C
Final Results...+PASS*
```



Sample printout from the optional thermal printer

Dimensions

Height: 6.6" (168 mm)
Width: 7.6" (193 mm)
Length: 8.5" (216 mm)
Weight: 3.2lbs (1.5 kg)

Electrical

Type: AC to DC power supply
Input: 100-240VAC; 50-60 Hz
Output: 20V DC; 2.5A

Interface

Type: Direct connect or Bluetooth
Direct cable length: 1 meter
Bluetooth Range: 100 meters

Environmental

Operating Temperature:
40°F/5°C -105°F/41°C
Storage/Transit Temperature:
-40°F/-40°C to 140°F/60°C
Operating Humidity:
10-90% non-condensing
Storage Humidity:
5-95% non-condensing

Safety/Regulatory

- UL-CUL 1950
- FCC (Class B)
- VCCI (Class B)
- C-TICK
- EN 500082-1
- EN 55022 (Class B)



www.autoidsolutions.net

Sales, Support, and Calibration +1.866.828.8643
701 Decatur Ave N 106, Minneapolis, MN 55427